Top view

254
212.62
206
210.56
204
180
13
4.62

A — A

Label Area
0.4 Recessed

Section A-A

95
6
6
3.10
3
88.50

Inner view (Top)

241.74
214.34
191.84
164.24
80
150
225

$\varnothing$ 5.50 x 4
$\varnothing$ 3 x 4

Side view

25
95
70
6

Inner view (Bottom)

243.93
216.93
193.93
166.93
150
70
70
30
190
225

$\varnothing$ 2.27 x 4
$\varnothing$ 6 x 4
for M3 x 12

Exploded view

Top Lid
Lid Screw
PCB Screw
Option :
Mounting Plate
(STC580)
Bottom Box
Option :
Mounting Feet
(MF0050)

RP1610 Sealed Enclosure
Size: 250 x 200 x 95 mm.
Material: Polycarbonate,(UL-94V2).
Color: Off White.
Working temp: -35˚c ~ 130˚c
Waterproof: IP65 / IP67
Supply:
1, Stainless fixing screw x 4 pcs.
2, Gasket x 1.
3, PCB screw x 4 pcs.
Option:
1, RP1610C: PC Clear Lid.
2, Mounting plate: STA580 (Metal).
3, Mounting plate: STC580 (ABS).
4, MF0050: Mounting Feet x 4 pcs.
5. RP1630: (250 x 200 x 130 mm)

Design	Check	Confirm	File	Date	Scale
William				2020.7.20	

RITEC Enclosures Inc.
10F, 85, Sec. 1, Kuang Fu Rd., San Chung,
Taipei, Taiwan, R.O.C.
Tel: 886-2-2999 8918   Fax: 886-2-2999 8955

RP1610 Dimensions

250 x 200 x 95 mm.

Ver.
Page
1/1